

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 635 557 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
01.03.2000 Bulletin 2000/09

(51) Int. Cl.<sup>7</sup>: **C10G 65/00**

(21) Application number: **94305037.7**

(22) Date of filing: **08.07.1994**

**(54) Middle distillate fuel production**

Herstellung von Mitteldestillatbrennstoff  
Production de distillats moyens

(84) Designated Contracting States:  
**DE FR GB IT NL**

(30) Priority: **22.07.1993 US 96129**

(43) Date of publication of application:  
**25.01.1995 Bulletin 1995/04**

(73) Proprietor:  
**EXXON RESEARCH AND ENGINEERING  
COMPANY  
Florham Park, New Jersey 07932-0390 (US)**

(72) Inventors:  
• **Davis, Stephen Mark  
Baton Rouge, Louisiana 70817 (US)**

• **Ryan, Daniel Francis  
Baton Rouge, Louisiana 70820 (US)**

(74) Representative:  
**Somers, Harold Arnold et al  
ESSO Engineering (Europe) Ltd.  
Patents & Licences  
Mailpoint 72  
Esso House  
Ermyrn Way  
Leatherhead, Surrey KT22 8XE (GB)**

(56) References cited:  
**EP-A- 0 161 833                      EP-A- 0 237 655  
EP-A- 0 321 301                      US-A- 3 681 232**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

[0001] This invention relates to the production of middle distillates, suitable for use as, or in, diesel or jet fuels, having excellent low temperature properties. More particularly, this invention relates to the production of such distillate fuels from a waxy hydrocarbon produced by the reaction of CO and hydrogen, for example in a Fischer-Tropsch hydrocarbon synthesis process.

[0002] The waxy product of a hydrocarbon synthesis product, particularly the product from a cobalt based catalyst process, contains a high proportion of normal paraffins. Nevertheless, the products from hydrocarbon synthesis must be useful in a wide variety of applications, just as are the products from naturally occurring petroleum. Indeed, the products must be fungible and the application must not be affected by the source of the product. Waxy products provide notoriously poor cold flow properties making such products difficult or impossible to use where cold flow properties are vital, e.g., lubes, diesel fuels, jet fuels.

[0003] Cold flow properties can be improved by increasing the branching of distillates within the proper range as well as by hydrocracking heavier components. Hydrocracking, however, produces gaseous and light products that tend to reduce the yield of valuable distillates, and there remains a desire for maximizing distillates obtained from Fischer-Tropsch waxes.

[0004] EP-A-0471524 discloses a method for producing a light oil of low viscosity and high viscosity index out of a heavy bottoms fraction boiling above a cut-off temperature in the range 580-600°C, obtained by the fractionation of isomerate produced by the hydroisomerization of heavy waxes, said method comprising the steps of severely hydrotreating the heavy bottoms fraction over a catalyst and re-fractionating the severely hydrotreated fraction. The said severe hydrotreating conditions may include a temperature in the range of from 300 to 500°C, a pressure in the range 500 to 5000 psig (3.45 to 34.48 MPa), a hydrogen treat gas rate of 250 to 5000 SCF H<sub>2</sub>/bbl feed (0.0445 to 0.89 m<sup>3</sup>H<sub>2</sub>/liter feed) and a space velocity of 0.1 to 10.0 v/v/hr. A suitable catalyst may be selected from the metals, oxides and sulfides of Group VIB and non-noble Group VIII on a refractory metal oxide support. The method may comprise a dewaxing step performed prior to or after the re-fractionation step. The said re-fractionation step may be practised to recover the oil fraction boiling in the 330°C to 580°C-600°C range. The severely hydrotreated bottoms fraction may be subjected to mild condition hydroisomerization prior to re-fractionation.

[0005] The present invention provides a process for producing middle distillate transportation fuel components from the waxy product of a hydrocarbon synthesis process which comprises:

(a) separating the said waxy product into a heavier fraction boiling above 500°F (260°C) and at least one lighter fraction boiling below 500°F (260°C), and separately recovering the said heavier and lighter fractions;

(b) catalytically isomerizing the said heavier fraction recovered in step (a) in the presence of hydrogen and recovering desired products with improved cold flow properties;

(c) catalytically hydrotreating at least one lighter fraction and removing heteroatom compounds therefrom;

(d) catalytically isomerizing the product of step (c) to produce a desired fuel component product having a freeze point of -30°F (-34°C) or lower.

[0006] The lighter fraction preferably boils in the range C<sub>5</sub>-500°F (260°C), e.g., in the range of from 320-500°F (160-260°C).

[0007] The heavier fraction preferably is substantially free of materials boiling below 500°F (260°C), e.g., preferably it contains less than about 3% hydrocarbons boiling below 500°F (260°C).

[0008] Preferably, at least a portion of the product of step (b) is combined with at least a portion of the product of step (d). Preferably, at least a portion of the product boiling in the range 320-500°F (160-260°C) from step (b) is combined with at least a portion of product boiling in the range 320-500°F (160-260°C) of step (d).

[0009] The product recovered from step (b) preferably boils in the range 320-700°F (160-370°C), preferably 500-700°F (260-370°C). Preferably, the product recovered from step (d) boils in the range 320-500°F (160-260°C).

[0010] The process of the present invention tends to increase the yield of distillates, such as kerosene, diesels, and lube base stocks as well as providing excellent cold flow properties that are essential for the utility of these materials. In accordance with this invention, materials useful as diesel and jet fuels or as blending components for diesel and jet fuels are produced from waxy Fischer-Tropsch products by a process comprising: separating (by fractionation) the waxy Fischer-Tropsch product into a heavier fraction boiling above about 500°F (260°C) and at least one lighter fraction boiling below about 500°F (260°C), for example, a 320/500°F fraction but preferably an all remaining liquid, at atmospheric pressure, fraction, i.e., a C<sub>5</sub>/500°F (260°C) fraction.

[0011] The heavier fraction is catalytically hydroisomerized, preferably in the absence of intermediate hydrotreating,

and produces products with excellent cold flow characteristics that can be used as jet fuels and diesel fuels or as blending components therefor. Preferably this isomerized material produces jet fuels having a freeze point of about -40°F (-40°C) or lower and diesel fuels having low cloud points, and cetane ratings less than that of the corresponding normal paraffins; thus, indicating increased product branching relative to the waxy paraffin feed.

[0012] The lighter fraction, either the 320/500 (160-260°C) cut or the C<sub>5</sub>/500 (C<sub>5</sub>/260°C) cut, is first subjected to mild catalytic hydrotreating to remove hetero-atom compounds, such as oxygenates, followed by catalytic hydroisomerization thereby producing materials also useful as diesel and jet fuels or useful as blending components therefor. Optionally, all or a part of each product stream can be combined or blended and used as diesel or jet fuels or further blended for such use.

[0013] The catalysts useful in each hydrotreating and hydroisomerization can be selected to improve the qualities of the products.

[0014] In one embodiment of this invention, any 700°F+ (371°C+) materials produced from either hydroisomerization step can be recycled or fed to the hydroisomerization step for the heavier fraction for further conversion and isomerization of the 7000°F+ (371°C+) fraction.

#### BRIEF DESCRIPTION OF THE DRAWING

[0015]

Figure 1 is a schematic arrangement of the process and its embodiments.

#### DETAILED DESCRIPTION

[0016] The Fischer-Tropsch process can produce a wide variety of materials depending on catalyst and process conditions. Currently, preferred catalysts include cobalt, ruthenium and iron. Cobalt and ruthenium make primarily paraffinic products, cobalt tending towards a heavier product slate, e.g., containing C<sub>20</sub>+, while ruthenium tends to produce more distillate type paraffins, e.g., C<sub>5</sub>-C<sub>20</sub>. Regardless of the catalyst or conditions employed, however, the high proportion of normal paraffins in the product must be converted into more useable products, such as transportation fuels. This conversion is accomplished primarily by hydrogen treatments involving hydrotreating, hydroisomerization, and hydrocracking. Nevertheless, the feed stock for this invention can be described as a waxy Fischer-Tropsch product, and this product can contain C<sub>5</sub>+ materials, preferably C<sub>10</sub>+, more preferably C<sub>20</sub>+ materials, a substantial portion of which are normal paraffins. A typical product slate is shown below, which can vary by ± 10% for each fraction.

TABLE A

Typical product slate from F/T process liquids:		
		Wt%
IBP - 160°C	IBP - 320°F	13
160 - 260°C	320 - 500°F	23
260 - 371°C	500 - 700°F	19
	700 - 1050°F	34
565°C+	1050°F+	11
		100

[0017] The feed stock is separated, usually by fractionation into a heavier fraction and at least one lighter fraction. The heavier fraction, preferably a 500°F+ (260°C+) fraction is substantially free of 500°F- (260°C-) materials. Preferably, the heavier fraction contains less than about 3 wt% 500°F-. We have found that hydrotreatment of this fraction, while allowing for increased conversion upon hydroisomerization, does not provide the excellent cold flow properties that can be obtained by hydroisomerization of an untreated fraction. Consequently, the heavier fraction is preferably subjected to catalytic hydroisomerization in the absence of any prior hydrotreating step. In other words the heavier fraction is not subjected to any chemical or catalytic treatment prior to hydroisomerization.

[0018] Hydroisomerization is a well known process and its conditions can vary widely. For example, Table B below lists some broad and preferred conditions for this step.

TABLE B

CONDITION	BROAD RANGE	PREFERRED RANGE
temperature, °F (°C)	300-800 (149-427)	650-750 (343-399)
gauge pressure, psig (bar.gauge)	0-2500 (0-172)	500-1200 (34-83)
hydrogen treat rate, SCF/B (m <sup>3</sup> /m <sup>3</sup> )	500-5000 (88.9-889.5)	2000-4000 (355.8-711.6)
hydrogen consumption rate, SCF/B	50-500 (8.89-88.9)	100-300 (1.78-5.34)

[0019] While virtually any catalyst may be satisfactory for this step, some catalysts perform better than others and are preferred. For example, catalysts containing a supported Group VIII noble metal, e.g., platinum or palladium, are useful as catalysts containing one or more Group VIII base metals, e.g., nickel, cobalt, which may or may not also include a Group VI metal, e.g., molybdenum. The support for the metals can be any refractory oxide or zeolite or mixtures thereof. Preferred supports include silica, alumina, titania, zirconia, vanadia and other Group III, IV, VA or VI oxides, as well as Y sieves, such as ultrastable Y sieves. Preferred supports include alumina and silica-alumina where the silica concentration of the bulk support is less than about 50 wt%, preferably less than about 35 wt%. More preferred supports are those described in US patent 5,187,138 incorporated herein by reference. Briefly, the catalysts described therein contain one or more Group VIII metals on alumina or silica-alumina supports where the surface of the support is modified by addition of a silica precursor, e.g., Si (OC<sub>2</sub>H<sub>5</sub>)<sub>4</sub>. Silica addition is at least 0.5 wt% preferably at least 2 wt%, more preferably about 2-25 wt%.

[0020] One factor to be kept in mind in hydroisomerization processes is that increasing conversion tends to increase cracking with resultant higher yields of gases and lower yields of distillate fuels. Consequently, conversion is usually maintained at about 35-80% of feed hydrocarbons boiling above 700°F (371°C) converted to hydrocarbons boiling below 700°F (371°C).

[0021] The cold flow properties of the resulting jet fuel (320/500°F, 160/260°C) fraction and diesel fuel (500/700°F, 260/371°C) fraction are excellent, making the products useful as blending stocks to make jet and diesel fuels.

[0022] At least one lighter fraction boiling below 500°F (260°C) is also recovered and treated. The lighter fraction can be a 320-500°F (160-260°C) fraction or preferably the entire liquid fraction boiling below 500°F (260°C), that is, the C<sub>5</sub>/500° (260°C) fraction. In either case the treatment steps are the same. First, the lighter fraction is hydrotreated to remove hetero-atom compounds, usually oxygenates formed in the hydrocarbon synthesis process. Hydrotreating temperatures can range from about 350-600°F (177-315°C), pressures from about 100-3000 psig (6.9-207 bar gauge) and hydrogen consumption rates of about 200-800 SCF/B feed (35.6-142.3 m<sup>3</sup>/m<sup>3</sup>). Catalysts for this step are well known and include any catalyst having a hydrogenation function, e.g., Group VIII noble or non-noble metal or Group VI metals, or combinations thereof, supported on refractory oxides or zeolites, e.g., alumina, silica, silica-alumina; alumina being a preferred support.

[0023] Turning to the drawing, hydrogen and CO enter Fischer-Tropsch reactor 10 where the synthesis gas is converted to C<sub>5</sub>+ hydrocarbons. A heavier fraction is recovered in line 12 and hydroisomerized in reactor 16. The useful product, a 320-700°F (160-371°C) fraction is recovered in line 22 and may be used as diesel or jet fuel or as blending components therefore after fractionation (not shown). In one embodiment, the 700°F+ (371°C+) material is recovered from the product in line 18 and recycled to the reactor 16. In another embodiment the light naphtha, e.g., C<sub>5</sub>/320°F (260°C) naphtha is flashed in line 20 and sent to hydrotreater 15 or optionally by line 26 to the overhead line 13 containing C<sub>5</sub>/320°F (260°C) naphtha for collection and storage.

[0024] The light fraction, in line 11 may be a 320/500°F (160/260°C) fraction or a C<sub>5</sub>/500°F (260°C) fraction. In the latter case overhead line 13 does not exist, in the former it collects the light naphtha, i.e., the C<sub>5</sub>/320°F (160°C) fraction. The lighter fraction is hydrotreated in hydrotreater 15 and the resulting light naphtha is flashed in line 17 to line 13. The 320/500°F (160/260°C) fraction is recovered in line 19 and hydroisomerized in reactor 21. The resulting product in line 23 may be used as jet fuel or as a blending agent therefor, and optionally may be combined via line 25 with product from reactor 16 in line 24. Light naphtha is flashed from reactor 21 and recovered in line 27.

[0025] After hydrotreating the lighter fraction, the light naphtha is flashed off and the remaining material is subjected to hydroisomerization. The catalyst can be any catalyst useful in hydroisomerization of light fractions, e.g., 320/500°F (160/260°C) fractions, and preferably contains a supported Group VIII noble metal. The noble metal catalysts containing platinum or palladium as described in US 5,187,138 are preferred.

TABLE C

CONDITION	BROAD RANGE	PREFERRED RANGE
temperature, °F (°C)	300-800 (149-427)	600-750 (343-399)
pressure, psig (bar, gauge)	50-2000 (3.5-138)	700-1200 (34-83)
hydrogen treat rate, SCF/B	500-5000 (88.9-889.5)	2000-4000 (355.8-711.6)
hydrogen consumption rate, SCF/B	50-500 (8.89-88.9)	100-300 (7.8-53.4)

[0026] In catalytic hydroisomerization reactions feed cracking should be maintained as low as possible, usually less than 20% cracking, preferably less than 10%, more preferably less than about 5%.

[0027] The following examples will serve to illustrate further this invention.

#### EXAMPLE 1

[0028] A series of six catalysts (A-H) was investigated for isomerization of a non-hydrotreated Fischer-Tropsch wax material with an initial boiling point of about 5000°F (260°C) and an oxygen content of about 0.45 wt%. All of the catalysts were prepared according to conventional procedures using commercially available materials well known in the art. (Catalysts I through N were used in later experiments.) The tests were conducted in a small upflow pilot plant unit at 1000 psig, 0.5 LHSV, with a hydrogen treat gas rate near 3000 SCF/Bbl (533.7 m<sup>3</sup>/m<sup>3</sup>), and at temperatures of 650 to 750°F (343-399°C). Material balances were collected at a series of increasing temperatures with operation periods of 100 to 250 hours at each condition. The composition of the catalysts is outlined in Table 1. Table 1 also indicates the relative activity of the catalysts expressed as the reaction temperature needed to achieve 40-50% conversion of feed hydrocarbons boiling above 700°F (371°C) to hydrocarbons boiling below 700°F (371°C). Catalysts described as being surface impregnated with silica were prepared in accordance with US-A-5,187,138.

TABLE 1

CATALYST	COMPOSITION	REACTION T °F (°C)	700°F+ (371°C+) CON- VERSION (WT%)
A	12% Mo-0.5% Ni-3% Co on 10% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	726 (385)	46
B	12% Mo-0.5% Ni-3% Co on 20% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	705 (374)	46
C	12% Mo-0.5% Ni-3% Co on 27% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	705 (374)	44
D	4% surface impregnated silica on A	708 (376)	53
E	8% surface impregnated silica on A	696 (368)	44
F	16% surface impregnated silica on A	668 (353)	40
G	4% surface impregnated silica on 0.6% Pt on 10% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	707 (375)	39
H	4% surface impregnated silica on 0.7% Pd on 10% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	716 (380)	43
I	0.5% Pd on composite support with 20% Al <sub>2</sub> O <sub>3</sub> and 80% ultrastable-Y	---	--
J	6% surface impregnated silica on 0.3% Pd on 10% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	---	--
K	0.5% Pd on 75% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	---	--
L	0.5% Pd on composite support with 80% high silica zeolite Y and 20% Al <sub>2</sub> O <sub>3</sub>	---	--
M	7.0% F on 0.6% Pt/Al <sub>2</sub> O <sub>3</sub>	---	--

TABLE 1 (continued)

CATALYST	COMPOSITION	REACTION T °F (°C)	700°F+ (371°C+) CON- VERSION (WT%)
N	0.5% Pt on ultrastable-Y zeolite	---	--

[0029] Clearly, different catalysts displayed significant differences in wax conversion activity. The most active materials were those produced using a surface silica additive. However, for the purposes of this invention, activity is not a critical factor. More important factors include the selectivity for producing jet fuel and diesel fuel versus gas and naphtha and the quality of the resulting jet fuel and diesel; e.g., these products should approach or meet cold flow property specifications for use as transportation fuels.

[0030] Table 2 provides a comparison of product distributions, jet fuel freeze points, diesel pour points, and cetane ratings for operations carried out at 40-50% 700°F+ (371°C+) conversion. All the catalysts considered in this example showed more-or-less similar boiling range product distributions characterized by high selectivity to 320/500°F (160/260°C) jet fuel range hydrocarbons with low gas and naphtha make. Other catalysts (not shown) were also examined which did not show such favorable selectivities.

TABLE 2  
PRODUCT DISTRIBUTIONS AND COLD FLOW PROPERTIES

CATALYST	700°F (371°C) CONV. (%)	PRODUCT YIELDS				FREEZE POINT FOUR POINT		500/700°F	
		C1-C4	C5/320°F (65/160°C)	320/500°F (160/260°C)	500/700°F (260/371°C)	°F (°C)	°F (°C)	°F (°C)	°F (°C)
A	46	3.4	5.2	20.8	32.9	-13 (-25)	27 (2.8)	71	
B	46	3.5	5.7	21.8	32.4	-31 (-35)	-11 (-24)	68	
C	44	1.6	5.6	20.7	31.4	-21 (-29)	-11 (-24)	68	
D	53	2.0	7.3	25.0	32.0	-47 (-44)	-6 (-21)	66	
E	44	2.4	4.7	21.1	31.8	-31 (-35)	-11 (-24)	68	
F	40	1.7	4.8	21.3	27.9	-31 (-35)	-11 (-24)	68	
G	39	3.8	9.7	19.2	19.9	-26 (-32)	-17 (-27)	66	
H	43	1.4	6.4	24.9	22.7	-27 (-33)	-17 (-27)	69	

at 1000 psig/0.5 LHSV/2500-3000 SCF/Bbl-H2 (70 bar.gauge/0.5 LHSV/444.7-533.7 m<sup>3</sup>/m<sup>3</sup>)

[0031] Table 2 shows that only certain catalysts combine high activity and jet/diesel selectivity in achieving cold flow properties. Specifically, Catalyst A was not able to produce jet fuel with acceptable cold flow properties. However, catalysts containing the same metal combination and loadings on silica-alumina supports with 20-30 wt% silica content (B

and C) provided acceptable performance. Also, CoNiMo/10% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub> catalysts which were modified by the addition of an additional 4-16 wt% silica as surface impregnated silica (catalysts D-F) also provided good performance. Good performance was also recognized with surface silica modified catalysts containing platinum or palladium (G,H) in place of CoNiMo. These types of catalysts (represented by B-H) produced products of similar overall quality and are strongly preferred for the wax isomerization step for 500°F+ (260°C+) material.

## EXAMPLE 2

[0032] Catalyst D (4% SiO<sub>2</sub>/CoNiMo/10% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub>) was tested for 500°F+ (260°C+) wax conversion activity, selectivity, and product quality under several different sets of processing conditions. In these tests, the catalyst was in the form of 1/20" (1.27 mm) quadrilobe extrudates in a 200 cm<sup>3</sup> pilot plant reactor. Table 3 summarizes results of these studies which employed the same non-hydrotreated wax feed as in Example 1. Activity was improved with equivalent selectivity and jet fuel quality when the (gauge) pressure was lowered to 500 psig (34.5 bar) and space velocity was increased to 1.0 LHSV. However, when the wax feed rate was increased to 3.0 LHSV and the temperature also increased, the selectivity pattern changed dramatically, e.g., the yield of jet fuel was lowered in favor of gas and naphtha production, and the quality of the jet fuel was also impaired as reflected by an increased freeze point. The detailed reasons for this change in selectivity are not fully understood, although pore diffusion limitations are believed to be a primary factor contributing to the inferior performance at 3 LHSV.

TABLE 3

<u>CONDITIONS</u>	<u>RELATIVE RATE CONSTANT FOR 700°F+ (371°C+) CONVERSION</u>		<u>SELECTIVITY</u>
1. { 700°F/1000 psig/0.5 LHSV (371°C/70 bar gauge/0.5 LHSV)	1.0-Base		Base
2. { 700°F/500 psig/1.0 LHSV (371°C/34.5 bar gauge/1.0 LHSV)	2.0		Base
3. { 725°F/1000 psig/3.0 LHSV (385°C/70 bar gauge/3.0 LHSV)	4-5		-8% jet/diesel; +7% gas/naphtha

## EXAMPLE 3

[0033] Several tests were also carried out using a 550°F+ (288°C+) Fischer-Tropsch wax which was hydrotreated to remove small levels of oxygen-containing hydrocarbons (alcohols, aldehydes, etc.) prior to isomerization. Hydrotreating was carried out at 635°F (335°C), 1000 psig (70 bar gauge), 2500 scf/Bbl H<sub>2</sub> (444.7 m<sup>3</sup>/m<sup>3</sup>) treat rate, and at space velocities of 0.5 to 3.0 LHSV using a commercial sulfided NiMo/Al<sub>2</sub>O<sub>3</sub> catalyst. Wax isomerization and hydrocracking was subsequently carried out using Catalyst B at 1000 psig (70 bar gauge), 0.5-3.0 LHSV, and 620-660°F (327-349°C). Results from these tests are compared with single stage isomerization operations in Table 4. The reactivity of the Fischer-Tropsch wax for conversion during isomerization was increased greatly by prehydrotreating. For example, 50% 700°F+ (371°C+) conversion was achieved near 600°F (315°C) with the hydrotreated wax versus a temperature requirement near 700°F (371°C) with the non-hydrotreated wax. However, the quality of the jet fuel produced with hydrotreating followed by isomerization was not as good as that achieved with single stage operations. Based on this behavior, wax isomerization is preferably carried out using non-hydrotreated 500°F+ (260°C+) Fischer-Tropsch product.



TABLE 4

500°F+ (260°C+) Feed	Reaction T °F (°C)	700°F+ (371°C+) Conversion (%)	Product Properties at 75°F	
			320/700°F (160/371°C)	700°F+ (371°C+)
Non-hydrotreated	716 (380)	57	clear liquid	clear liquid
Hydrotreated	608 (320)	56	cloudy, waxy liquid	hard wax
at 1000 psig, 0.5 LHSV, 2500 SCF/Bbl (70 bar gauge, 0.5 LHSV <sup>1</sup> , 444.7 m <sup>3</sup> H <sub>2</sub> /m <sup>3</sup> oil)				

**EXAMPLE 4**

[0034] Tests were also carried out using Fischer-Tropsch wax feeds with variable contents of 500°F- (260°C-) hydrocarbons. As shown in Table 5 for similar levels of 700°F+ (371°C+) feed conversion, the quality of the 320/500°F (160/260°C) jet fuel (judged from freeze point measurements) improved as the 500°F- (260°C-) content on feed decreased. In order to meet jet fuel freeze point specifications at 700°F+ (371°C+) conversion levels near 50-60%, the content of 500°F- (260°C-) hydrocarbons on wax feed is less than about 6%, preferably less than 4 wt%, and most preferably less than 2 wt%.

TABLE 5

At 50% 700°F+ (371°C+) Conversion to 700°F- (371°C-) Material	
Wt% 500°F (260°C) in Wax	Freeze Pt. of 320/500°F (160/260°C) Jet Component
5.5	-33°C (-27°F)
1.5	-45°C (-49°F)

**EXAMPLE 5**

[0035] Catalyst H of Example 1 and catalyst I were evaluated for isomerization of a light oil Fischer-Tropsch product boiling between 100°F (38°C) and 500°F (260°C) (approximating a C<sub>5</sub>/500°F (C<sub>5</sub>/260°C) fraction). The reaction conditions were similar to those described in Example 1. Catalyst I was a commercially available hydrocracking catalyst containing 0.5 wt% Pd dispersed on a particulate support material containing about 80 wt% ultrastable-Y zeolite and 20 wt% alumina. Little or no conversion of this feed could be accomplished with either catalyst for reaction temperatures up to 750°F (399°C).

**EXAMPLE 6**

[0036] The same feed employed in Example 4 was subjected to hydrotreating and fractionation before isomerization tests were conducted. Hydrotreating was carried out at 350 psig (24.1 bar gauge), 450°F (232°C), and 3 LHSV using a 50% Ni/Al<sub>2</sub>O<sub>3</sub> catalyst. After hydrotreating, the feed was topped to an initial boiling point of about 350°F (177°C) prior to isomerization tests. The isomerization tests were carried out at 350-600 psig (24-41 bar gauge), 550-700°F (288-371°C), and 1 LHSV using catalysts J and L described in Table 1. In contrast to Example 4, the hydrotreated distillate feed showed good reactivity for conversion to naphtha and isomerized distillate range hydrocarbons that are suitable for use as diesel and jet fuel blending components. At high levels of 500°F+ (260°C+) conversion, the 320/500°F (160/260°C) product produced over catalyst J was suitable for use as jet fuel without further blending. This catalyst contained 0.3 wt% palladium dispersed on a 10% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub> support which was further modified by the addition of 6 wt% surface silica derived from impregnation of Si(OC<sub>2</sub>H<sub>5</sub>)<sub>4</sub>. This catalyst displayed a superior selectivity for jet fuel production versus gas and naphtha as compared to the more active catalysts K and L which contained 0.5% palladium dispersed on supports containing 75% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub> and ultrastable-Y zeolite, respectively. Table 6 compares product

distributions and jet quality at several conversion levels.

TABLE 6

HYDROISOMERIZATION OF HYDROTREATED 350/500 F-T DISTILLATE					
CATALYST	T °F (°C)	NC <sub>10+</sub> CONV.	PRODUCT YIELDS (WT%)		320/500°F (160/260°C) FREEZE PT (°F)
			C1/320°F (160°C)	320/500°F (160/260°C)	
Pd/US-Y	588.7 (309)	71.6	40.64	59.36	-38 (-39°C)
Pd/Si-enhanced TN-8 SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> (from U.S.-A- 5,187,138)	599.8 (315)	84.1	54.63	45.37	-51 (-46°C)

#### EXAMPLE 7

[0037] Isomerization tests were also carried out with the same hydrotreated 350°F+ (176.7°C+) distillate feedstock employed in Example 6 using catalyst K described in Table 1 and a lab catalyst prepared by impregnating 0.5 wt% palladium onto the same 20% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub> support that was used to produce catalyst B.

[0038] This catalyst was dried and calcined in air at 450°C for 3-4 hours prior to use. In this case, the test goal was to maximize the yield of 320-500°F (160-260°C) boiling range distillate satisfying a freeze point specification of -50°F (-45°C). Table 7 compares product yields under these conditions of constant product quality. It can be seen that the catalyst produced using the 20 wt% silica support provided improved distillate yield and reduced gas and naphtha make as compared to the catalyst produced using the high (75 wt%) silica content support, although both catalysts provided effective performance.

TABLE 7

Hydroisomerization of Hydrotreated 350/500°F (175/260°C) F-T Distillate		
Catalyst	0.5%Pd/20% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>	0.5%Pd/75% SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub>
Yield (wt%) at -50°F (-45°C) 320/500°F (160-260°C) Freeze Point		
C <sub>1</sub> -C <sub>4</sub> Gas	1.8	2.6
C <sub>5</sub> /320°F (160°C)	10.5	13.5
320/500°F (160/260°C)	82.5	77.7
500°F+ (260°C+)	5.4	6.5

#### EXAMPLE 8

[0039] Isomerization tests were also conducted using a second hydrotreated normal paraffin feedstock containing primarily distillate range hydrocarbons. In this case, six catalysts (A,D,G,H,M,N) were investigated at 1000 psig (70 bar gauge), 0.5 LHSV, and with temperatures ranging from 400°F (204°C) to 700°F (371°C). As shown in Table 8, very different activity and selectivity patterns were observed with the different catalysts. Catalysts A and D containing CoNiMo dispersed on silica-alumina supports showed high tendency for C<sub>1</sub>-C<sub>4</sub> gas make. Catalyst N which contained 0.5 wt% platinum on an ultrastable-Y zeolite showed high activity at low temperatures but the products were mostly naphtha range hydrocarbons. Catalyst M containing 0.6% Pt dispersed on a fluorided alumina showed good activity combined with good selectivity for producing isomerized hydrocarbons in the jet fuel boiling range. However, the best selectivities for producing 320/500°F (160/260°C) hydrocarbons versus gas and naphtha were obtained with noble metal catalysts

containing 0.6 wt% Pt or 0.7 wt% Pd dispersed on a 10% SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub> support which was further modified by the addition of 4 wt% surface silica derived from impregnation with Si(OC<sub>2</sub>H<sub>5</sub>)<sub>4</sub>.

TABLE 8

CATALYST	RXN T°F (°C)	500°F+ (260°C+) CONV (%)	PRODUCT YIELDS (WT%)			
			CH <sub>4</sub>	C <sub>2</sub> /C <sub>4</sub>	C <sub>5</sub> /320°F	320/500°F
A	658 (348)	78	4.1	1.6	8.7	69
	674 (357)	93	9.1	3.1	14.7	54
D	656 (347)	80	2.1	1.4	6.4	77
	674 (357)	92	4.7	2.5	14.4	62
G	656 (347)	78	0.02	0.65	4.9	84
	672	90	0.04	1.6	11.1	77
H	656 (347)	72	0.01	0.61	3.9	84
	671 (355)	88	0.01	1.3	9.0	80
M	590 (310)	58	0.01	0.85	4.1	79
N	400 (204)	52	0.01	7.6	25.4	47
at 1000 psig/0.5 LHSV/3000 SCF/Bbl-H <sub>2</sub> ; 32% 550°F+ (70 bar gauge/0.5 LHSV/533.7 m <sup>3</sup> /m <sup>3</sup> , 32% 288°C+) on feed						

### Claims

1. A process for producing middle distillate transportation fuel components from the waxy product of a hydrocarbon synthesis process which comprises:
  - (a) separating the said waxy product into a heavier fraction boiling above 500°F (260°C) and at least one lighter fraction boiling below 500°F (260°C), and separately recovering the said heavier and lighter fractions;
  - (b) catalytically isomerizing the said heavier fraction recovered in step (a) in the presence of hydrogen and recovering desired products with improved cold flow properties;
  - (c) catalytically hydrotreating at least one lighter fraction and removing hetero-atom compounds therefrom;
  - (d) catalytically isomerizing the product of step (c) to produce a desired fuel component product having a freeze point of -30°F (-34°C) or lower.
2. The process of claim 1 wherein the lighter fraction boils in the range C<sub>5</sub>-500°F (260°C).
3. The process of claim 2 wherein the lighter fraction boils in the range of from 320-500°F (160-260°C).
4. The process of any preceding claim, wherein the heavier fraction is substantially free of materials boiling below 500°F (260°C).
5. The process of claim 4, wherein the heavier fraction contains less than about 3% hydrocarbons boiling below 500°F (260°C).
6. The process of any preceding claim, wherein at least a portion of the product of step (b) is combined with at least a portion of the product of step (d).
7. The process of claim 6 wherein at least a portion of the product boiling in the range 320-500°F (160-260°C) from step (b) is combined with at least a portion of product boiling in the range 320-500°F (160-260°C) of step (d).

8. The process of any preceding claim, wherein the product recovered from step (b) boils in the range 320-700°F (160-370°C), preferably 500-700°F (260-370°C).
9. The process of any preceding claim, wherein the product recovered from step (d) boils in the range 320-500°F (160-260°C).

#### Patentansprüche

1. Verfahren zur Herstellung von Komponenten für Mitteldestillat-Transportmittelbrennstoffe aus dem wachsartigen Produkt eines Kohlenwasserstoffsyntheseverfahrens, bei dem:

(a) das wachsartige Produkt in eine schwerere über 260 °C (500 °F) siedende Fraktion und mindestens eine leichtere unter 260 °C (500 °F) siedende Fraktion getrennt wird und die schwerere und die leichtere(n) Fraktion(en) getrennt gewonnen werden,

(b) die in Stufe (a) gewonnene schwerere Fraktion in Gegenwart von Wasserstoff katalytisch isomerisiert wird und gewünschte Produkte mit verbesserten Kaltfließigenschaften gewonnen werden,

(c) mindestens eine leichtere Fraktion katalytisch mit Wasserstoff behandelt wird und daraus Heteroatomverbindungen entfernt werden,

(d) das Produkt aus Stufe (c) katalytisch isomerisiert wird, um ein gewünschtes Brennstoffkomponentenprodukt mit einem Gefrierpunkt von -34 °C (-30 °F) oder niedriger zu erzeugen.

2. Verfahren nach Anspruch 1, bei dem die leichtere Fraktion im Bereich C<sub>5</sub>-260 °C (500 °F) siedet.
3. Verfahren nach Anspruch 2 bei dem die leichtere Fraktion im Bereich 160 bis 260 °C (320 bis 500 °F) siedet.
4. Verfahren nach einem der vorhergehenden Ansprüche, bei dem die schwerere Fraktion im wesentlichen frei von unter 260 °C (500 °F) siedenden Materialien ist.
5. Verfahren nach Anspruch 4, bei dem die schwerere Fraktion weniger als etwa 3 % unter 260 °C (500 °F) siedende Kohlenwasserstoffe enthält.
6. Verfahren nach einem der vorhergehenden Ansprüche, bei dem mindestens ein Teil des Produkts aus Stufe (b) mit mindestens einem Teil des Produkts aus Stufe (d) kombiniert wird.
7. Verfahren nach Anspruch 6, bei dem mindestens ein Teil des im Bereich von 160 bis 260 °C (320 bis 500 °F) siedenden Produkts aus Stufe (b) mit mindestens einem Teil des im Bereich von 160 bis 260 °C (320 bis 500 °F) siedenden Produkts aus Stufe (d) kombiniert wird.
8. Verfahren nach einem der vorhergehenden Ansprüche, bei dem das aus Stufe (b) gewonnene Produkt im Bereich von 160 bis 370 °C (320 bis 700 °F), vorzugsweise im Bereich von 260 bis 370 °C (500 bis 700 °F) siedet.
9. Verfahren nach einem der vorhergehenden Ansprüche, bei dem das aus Stufe (d) gewonnene Produkt im Bereich von 160 bis 260 °C (320 bis 500 °F) siedet.

#### Revendications

1. Procédé de production de composants de carburants de transport formés de distillats moyens à partir du produit paraffiné d'un procédé de synthèse d'hydrocarbures, qui comprend les étapes consistant:

(a) à séparer ledit produit paraffiné en une fraction plus lourde bouillant audessus de 260°C (500°F) et en au moins une fraction plus légère bouillant au-dessous de 260°C (500°F), et à récupérer séparément lesdites fractions plus lourde et plus légère,

(b) à isomériser par voie catalytique ladite fraction plus lourde récupérée à l'étape (a) en présence d'hydrogène et à récupérer des produits souhaités ayant de meilleures propriétés rhéologiques à froid,

(c) à hydrotraiter par voie catalytique au moins une fraction plus légère et à en éliminer les composés hétéro-

atomiques, et

(d) à isomériser par voie catalytique le produit de l'étape (c) pour produire un composant de carburant souhaité ayant un point de congélation de -34°C (-30°F) ou moins.

2. Procédé selon la revendication 1, dans lequel la fraction plus légère bout dans la plage de C<sub>5</sub>-260°C (500°F).
3. Procédé selon la revendication 2, dans lequel la fraction plus légère bout dans la plage de 160-260°C (320-500°F).
4. Procédé selon l'une quelconque des revendications précédentes, dans lequel la fraction plus lourde est sensiblement exempte de matériaux bouillant en dessous de 260°C (500°F).
5. Procédé selon la revendication 4, dans lequel la fraction plus lourde contient moins d'environ 3% d'hydrocarbures bouillant en dessous de 260°C (500°F).
6. Procédé selon l'une quelconque des revendications précédentes, dans lequel au moins une partie du produit de l'étape (b) est combinée avec au moins une partie du produit de l'étape (d).
7. Procédé selon la revendication 6, dans lequel au moins une partie du produit de l'étape (b) bouillant dans la plage de 160-260°C (320-500°F) est combiné avec au moins une partie du produit de l'étape (d) bouillant dans la plage de 160-260°C (320-500°F).
8. Procédé selon l'une quelconque des revendications précédentes, dans lequel le produit récupéré à l'étape (b) bout dans la plage de 160-370°C (320-700°F), de préférence de 260-370°C (500-700°F).
9. Procédé selon l'une quelconque des revendications précédentes, dans lequel le produit récupéré à l'étape (d) bout dans la plage de 160-260°C (320-500°F).




FIG. 1